

04/04/2000 10:45 784945210: BONSAL TECHNICAL PAGE 01

(Mosaic Tile Grout)

61132-1000

MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

TRADE NAME: POLYMER MODIFIED SANDED TILE GROUT, COLORS & WHITE, CER & A/P
CHEMICAL FAMILY/SYNONYMS: Portland Cement Mortar
MANUFACTURER: W. R. BONSAL COMPANY, P.O. BOX 241148, CHARLOTTE, N. C. 28224
EMERGENCY PHONE: (704) 525-1621 Mr. Fred Goeman

SECTION II - HAZARDOUS INGREDIENTS

Table with 4 columns: DESCRIPTION, CAS#, PERCENT, OCCUPATIONAL EXPOSURE LIMITS (TLV, PEL), and VAPOR PRESSURE (MM HG). Rows include SILICONE DIOXIDE, RESPIRABLE DUST, PORTLAND CEMENT, SILICATES, CALCIUM CARBONATE, ADDITIVES, PIGMENT, IRON, CHROMIUM AND/OR CARBON BLACK, and TITANIUM DIOXIDE.

* % IS DETERMINED FROM AIRBORNE SAMPLES

SECTION III - PHYSICAL DATA

BOILING POINT (°F) N/A
VAPOR PRESSURE (mmHg.) N/A
VAPOR DENSITY (AIR=1) N/A
SOLUBILITY IN WATER: INSOLUBLE
SPECIFIC GRAVITY (H2O=1) 3.32
% VOLATILE BY VOLUME (%) 0
EVAPORATION RATE N/A

APPEARANCE & ODOR: WHITE, GREY OR COLORED POWDER, GRANULAR

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT: NON FLAMMABLE
EXTINGUISHING MEDIA: WATER
SPECIAL FIRE FIGHTING PROCEDURES: NONE REQUIRED
UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE EXISTING

Friedrich Goeman 12-17-99

61132-1000
2000
5120

04/04/2008 10:45 7049450104

BONSAL TECHNICAL

PAGE 02

MATERIAL SAFETY DATA SHEET
PRODUCT: POLYMER MODIFIED SANDED TILE GROUT

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: Respirable Dust - TLV 0.1 MG/M³
 EFFECTS OF OVEREXPOSURE: Excess exposure by inhalation over an extended period of time may result in the development of pulmonary diseases including pneumoconiosis and silicosis. Prolonged contact may cause skin irritation or dermatitis. Skin and eye irritant.
 EMERGENCY FIRST AID: Inhalation: remove from exposure. If not breathing, give artificial respiration, if breathing difficult, give oxygen, consult a physician. Eye Contact: flush thoroughly with water for 15 minutes. Consult a physician. Skin Contact: wash thoroughly with soap and water.

SECTION VI - REACTIVITY DATA

STABILITY: UNSTABLE _____ STABLE X
 CONDITIONS TO AVOID: N/A
 INCOMPATIBILITY (MATERIALS TO AVOID): Highly alkaline. Strong acids may cause violent, exothermic reaction, evolve toxic gases/vapors, depending on type acid.
 HAZARDOUS DECOMPOSITION PRODUCTS: N/A
 HAZARDOUS POLYMERIZATION: MAY OCCUR _____ WILL NOT OCCUR X
 CONDITIONS TO AVOID: N/A

SECTION VII - SPILL OR LEAK PROCEDURES

IN CASE MATERIAL IS RELEASED OR SPILLED: Use personal protective equipment to prevent dust exposures and protect against alkali burns or irritation. Sec. 8.
 WASTE DISPOSAL METHOD: Dispose of in accordance with Federal, State and local regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (TYPE): NIOSH/MSHA approved for protection against silica and nuisance dusts.
 VENTILATION:
 Local Exhaust: Yes Special:
 Mechanical: _____ Other: _____
 PROTECTIVE GLOVES: Rubber, PVC, Neoprene EYE PROTECTION: Goggles
 OTHER PROTECTIVE EQUIPMENT: Rubber boots, arm sleeves and aprons when necessary to prevent skin contact.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS IN HANDLING AND STORING: Store in manner to prevent contact with strong acids. Avoid contact with water to preserve product.
 OTHER PRECAUTIONS: None

238

Page 2 of 2